

- ▶ 5-8M 360 degrees pickup radios ► Full-Duplex Communication Automatic Noise Reduction & Echo Cancellation Simple setup and stable connection
 - Compatible with various devices Applicable to 60 square meters conference room with Extension

 - 360° Voice Pick-Up **Noise Cancellation** Wireless adapter








connection




call experience for you.



omnidirectional Microphone with a transmission distance of up to 5 meters, which can achieve 360" voice pick-up, so calls sound their best on both ends. Which can bring you a good interactive experience and create the best conference







vidtel 🗰 webex

RADVISION'

Delivering the Visual Experience

WIDE COMPATIABLITY

MULTIPLE CONNECTION METHODS

Multiple connection mode, compatible with various devices, multiple interfaces, can be connected to computers, all-in-

Compatible with mainstream online voice calling services (PolyCom, Blue Jeans, Cisco, Vmix, GoToMeeting, Radvision,


SeeVogh, WebEx, Easy meeting, Vidtel and working with Microsoft Lync Software, and ZOOM.US, SKYPE, VIDYO etc), you can enjoy great sound quality and comfort at the same

. 1 | 1 . 1 | 1 .

GoToMeeting

vMix

BlueJeans



time.

Polycom[®]













L> Lync

Nidyo° Vidyo°

up to 4 hours, up to 10 hours use after a full charge

Build-in 4000mAh lithium Rechargeable battery, full charge in

LONG BATTERY LIFE

| 4000mAh

Working statusindicator

Hang up the call

Volume increases

ONLINE EDUCATION

10

0.81KG

152*152*40mm

495*405*220mm

0.69KG

15-30 SQM

30-60 SQM

Full frequency reproducer

Max output 5W, effective 3W

Support

supplies power to the CM600 device through

Battery specification: 4000mAh; Full charge time: 4 hours (5V/2A);

Maximum charging current: 2A;


0°C-40C

Windows 7, Windows 8, Windows 10, Linux,

Omnidirectional microphone, USB cable,

Duration: 10 hours;

TOUCHABLE SMART BUTTON



mute -

APPLICATION SCENARIOS

VIDEO CONFERENCING

Packing quantity(Pcs)

Packing weight (g)

Product dimension

Packing weight (g)

Covering area

Covering area

(+Extension Unit)

Reproducer type

Noise suppression

Power supply

Rechargeable battery

Work temperature

System Requirements

Package contents

Rate of power

Carton) Carton Dimensions

(Length×width×Height mm)

(W×H mm)

Wireless connection

status light



Product weight(g) 0.36KG Material PC/ABS Package dimension 199*189*94mm (L×W×H mm) Carton) Carton Dimensions 10 (Length×width×Height mm)

Specification(Extension Unit)

Microphone Microphone type Omnidirectional microphone Pickup distance 4-8 meters **SNR** 65dB A circular array of built-in four Microphone array omnidirectional microphones, 360° pick-up Frequency response 100Hz~22kHz

Reproducer

Meeting capacity

85dBA (in the range of 1m) Volume Sensitivity 85 dB SPL (in the range of 0.5m) Frequency range 150Hz ~ 22kHz **Audio frequency**

48K Sampling rate, HD broadband audio, **Audio features** full duplex audio **USB** protocol **UAC 2.0** Echo cancellation Support

Support Gain control **Connection mode** USB Dongle, Wireless adapter wireless receiving distance 10 meters USB A interface, the external power supply

the USB B interface; **Light touch button** (mute button with light indicator) button Connect with terminal equipment through Line in/out 3.5mm four-core audio cable USB data communication, audio input/call **USB** wired

An extension unit can be added through an **Extension ports** RJ45 extension cable

Environment condition

CCC, CE, RoHS, FCC Certification Color Black Packing type Leather box

Others

Mac OS X, Android

Quick start guide